



DIFFERENTIAL THERMAL ANALYZER BANA-102

DIFFERENTIAL THERMAL ANALYZER BANA-102

Differential Thermal Analysis is a technique which can measure the temperature difference and temperature relationship between the sample and the reference material in the process control temperature. Differential thermal analysis curves can describe the relationship of the temperature difference ΔT changes with the temperature or time between the sample and the reference material.

Used in Metallurgy, Semiconductor, Pharmaceutical, Food Testing, Cement Chemistry, Environmental Research.
Also known as DTA Analyzer.

BANA-102 DIFFERENTIAL THERMAL ANALYZER



The main control chip of the instrument adopts Cortex-M3 core ARM controller, which has faster operation speed and more accurate temperature control.

USB two-way communication makes the operation more convenient.

Adopt 7 inch 24bit color LCD touch screen, the interface is more friendly.

Adopt Ni Cr alloy sensor, more resistant to high temperature, corrosion and oxidation.

SPECIFICATIONS

Model	BANA-102
Display	24 bit color 7 inch LCD touch screen display
Temperature Range	Room temperature ~ 1350 °C
Measuring Range	0~±2000 μ V
DTA Precision	±0.1 μ V
Heating Rate	1 ~ 80°C/min
Temperature Resolution	0.1°C
Temperature Accuracy	±0.1°C
Temperature Repeatability	±0.1°C
Temperature Control	
Cooling Temperature	program control
Constant Temperature	air-cooled program control
Body Structure	Use the structure of the cover to replace the traditional lifting furnace, with high precision and easy operation
Atmosphere Control	(optional) gas flow meter, atmosphere conversion device
Data Interface	standard USB connector, supporting data line and operating Software
Parameters of Standard	Equipped with reference substances, with a key calibration function (User can correct the temperature)
Work Power	AC 220V 50Hz



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com