



## VERTICAL AUTOCLAVE BAVT-2901

# VERTICAL AUTOCLAVE BAVT-2901

## BAVT-2901 VERTICAL AUTOCLAVE



- Three times pre-vacuum
- High quality stainless steel material
- Microcomputer automatic control, arbitrary setting sterilization parameters
- Safety interlocking device
- LED touch screen display
- Standard test interface
- Self-expanding seal
- With drying function
- With stainless steel bucket or basket
- With automatic protection function: over temperature protection; over pressure self discharge protection ; low water level protection; anti dry burning.
- Automatic water
- External steam Generator
- Buzzer reminder after sterilization, automatic stop.
- Automatic discharge of cold air, automatic steam exhaust after sterilization
- Internal printer

## SPECIFICATIONS

Model	BAVT-2901
Capacity	35 L
Power	3.5 kW
Voltage	AC 220V, 50HZ
Design pressure	0.25 Mpa
Design temperature	139°C
Rated working pressure	0.22 Mpa
Rated working temperature	134°C
Sterilization temperature setting range	116°C-134°C
Sterilization time setting range	4 ~ 120 min
Drying time setting range	0 ~ 240 min
Chamber volume	Ø 350x400
Bucket dimension	Ø 330x320
Basket dimension	Ø 320x350
Outer dimension	698x498x940
Packing size	790x610x1130
Net weight	115 Kg
Gross Weight	130 Kg



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)