



WATER BATH BBWA-202

WATER BATH BBWA-202

Biolab Water bath provides precise temperature control along with stirring mixture function to create a stable temperature environment for a variety of applications. Easy to use and maintain, seamless stainless steel chamber with available with a digital operating system.

Used in Calibration tests, High temperature organic distillation, External circulation, High temperature experiments. Also known as Oil Bath, Bath Circulator, Laboratory Oil Bath Circulator.

BBWA-202 WATER BATH



- Stainless steel water sink with surface electrolysis treatment
- Cold rolled steel plated outer shell with surface electrolysis powder spray
- Stainless steel U type heating tube heater
- Touch button setting
- Measuring temperature: display on the three digital tubes upper row
- Setting temperature: display on the lower row
- Fixed temperature operation, timing function, auto stop
- Optional: Multi-section program control
- Additional function: Deviation correction, menu key lock, power failure back-up, power-off parameter memory, PID adjustable
- Thermal resistor sensor
- Over-temperature alarm, short-circuit protection

SPECIFICATIONS

Model	BBWA-202
Capacity	6.3 L
Heating Mode	Bottom heating, water temperature natural convection
Temperature Range	RT+5°C to 100°C
Temperature Resolution	0.1°C
Temperature Motion	±0.5°C
Temperature Uniformity	±1.0°C
Time Range	0~999 min
Cover Aperture	Φ 120 mm
Cover Material	PP Plastic
Cover Number per hole	5
Inner Dimension (WxDxH)	305x160x130 mm
Outer Dimension (WxDxH)	340x210x210 mm
Packaging size (WxDxH)	405x275x275 mm
Weight	4/5 kg
Power	600 W
Power Supply	220 V, 50 Hz 2.7 A



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com