



WATER BATH BBWA-205

WATER BATH BBWA-205

Biolab Water bath provides precise temperature control along with stirring mixture function to create a stable temperature environment for a variety of applications. Easy to use and maintain, seamless stainless steel chamber with available with a digital operating system.

Used in Enzyme reactions, Immunoassay, Incubation, Laboratory, Research, Medical, Pharmaceuticals.

Also known as Laboratory water bath.

BBWA-205 WATER BATH



Stainless steel water sink with surface electrolysis treatment

Cold rolled steel plated outer shell with surface electrolysis powder spray

Stainless steel U type heating tube heater

Touch button setting

Measuring temperature: display on the three digital tubes upper row

Setting temperature: display on the lower row

Fixed temperature operation, timing function, auto stop

Optional: Multi-section program control

Additional function: Deviation correction, menu key lock, power failure back-up, power-off parameter memory, PID adjustable

Thermal resistor sensor

Over-temperature alarm, short-circuit protection

SPECIFICATIONS

Model	BBWA-205
Capacity	12 L
Heating Mode	Bottom heating, water temperature natural convection
Temperature Range	RT+5°C to 100°C
Temperature Resolution	0.1°C
Temperature Motion	±0.5°C
Temperature Uniformity	±1.0°C
Time Range	0~999 min
Cover Aperture	Φ 120 mm
Cover Material	PP Plastic
Cover Number per hole	5
Inner Dimension (WxDxH)	305x305x130 mm
Outer Dimension (WxDxH)	340x350x210 mm
Packaging size (WxDxH)	415x415x275 mm
Weight	6/7 kg
Power	800 W
Power Supply	220 V, 50 Hz 3.6 A



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com