



## WATER BATH BBWA-2401

## WATER BATH BBWA-2401

### BBWA-2401 WATER BATH



PID temperature controller, large LCD display screen and interface provides for userfriendly operation

Easy to set Adjustable Timer. (1 minute to 5,999 minutes)

Maintenance-free operation with easy to clean surface

Both heater and bath chamber are made of corrosion-resistant stainless steel

No angle in bath chamber, easy to clean

The standard stainless-steel bottom plate, helps prevents direct contact by accessories and tubes to heating element and sensors

Drain valve makes emptying of bath water fast and easy for cleaning and moving

## SPECIFICATIONS

Model	BBWA-2401
Capacity	5 L
Power requirements	AC 220 V 50 HZ
Power	500 W
Temperature Range	RT+5 - 100°C
Temperature fluctuation	±0.2°C
Temperature resolution	0.1°C
Internal dimension	280Wx130Dx150H mm
External dimension	345Wx200Dx340H mm
Timer	1 - 5999 min
Net weight	5 Kg
Porous cover(lid)	2 - hole



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)