



CO2 INCUBATOR AIR JACKETED BCAJ-8204

CO2 INCUBATOR AIR JACKETED BCAJ-8204

BCAJ-8204 CO2 INCUBATOR AIR JACKETED



Touch screen controller, 72-hour machine operation record query function to help user tracking abnormal conditions and trace historical operation information

Faster CO2 concentration Restoration Speed

Infrared sensor can keep CO2 concentration stability and uniformity when door open frequently

Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable

Microorganism filter at inlet provides 99.99% filtration of bacteria and dust ($\Phi < 0.3\mu\text{m}$) and supplies pure CO2 into the incubator

Door temperature controller prevents dewfall on glass door of incubator effectively

Independent audible and visible temperature-limiting alarm system ensures experiments run safely

Alarm function for temperature difference, CO2 over concentration and concentration difference, door open time, UV working status

Auto-controller of fan speed to prevent damage to the samples

90°C high temperature and humidity sterilization function

SPECIFICATIONS

Model	BCAJ-8204
Capacity	190 L
Electrical Requirement	220 V 50 Hz
Screen	7" Touch screen
Power Consumption	750 W
Temperature range	RT+5 - 50°C
Ambient Temperature	+5 - 30°C
Temperature Stability	±0.1°C
CO2 Range	0 - 20% V/V
CO2 Control Resolution	±0.1%(IR sensor)
CO2 Recovery	(Door open 30s, recovery to 5%) ≤ 3min
Temperature Recovery	(Door open 30s, recovery to 37°C) ≤ 8min
Humidity Method	Natural vaporization ≥ 90%
Interior Dimension	520Wx530Dx690H mm
Exterior Dimension	708Wx710Dx1030H mm
shelves	3 pcs
Sterilization method	18hrs (90°C moist heat disinfection)



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com