



BENCHTOP HIGH SPEED REFRIGERATED CENTRIFUGE BCBHR-204

BENCHTOP HIGH SPEED REFRIGERATED CENTRIFUGE

BCBHR-204

Engineered to maximize productivity and reliably deliver a wide range of high speed separations. Stainless steel interiors, integrated refrigeration system and advanced temperature controls make it flexible for your evolving applications. Safety features and low noise operation make it an ideal partner for your day to day separations. Used in Cell Separation, Precipitation, Sample Processing, Clinical, Cell Culture, Microplate Processing, Biochemistry, medical diagnosis.

Also known as Floor Standing Centrifuge, Laboratory Floor Type Centrifuge, Floor Type Refrigerated Centrifuge, Benchtop Centrifuge, Laboratory Tabletop Centrifuge.

BCBHR-204 BENCHTOP HIGH SPEED REFRIGERATED CENTRIFUGE

Microcomputer controlled programmable operation with CPU control system that controls speed, temperature and relative centrifuge force

LCD wide screen displays set and run conditions for easy monitoring

Brushless DC Motor ensures low maintenance, high efficiency and constant speed of rotation

Store 10 programs in centrifuge memory which are retained even after powering down the centrifuge

Fully stainless steel structure and aluminium alloy rotor for sustainable use

Speed and the centrifugal force can be step adjusted (10 RPM/10xg)

High quality CFC-free compressor with two cycle refrigeration and high accuracy of temperature

Multiple layers of shock absorbers with auto balancing function

System is complemented by multiple new accessories, including tube racks, centrifuge adapters and rotors

Safety features: Self diagnostic, Rotor Identification, Rotor imbalance detector, Lid protection, Door Cover Protection, Built in electronic door lock and protection, Over speed protection, Over temperature protection

SPECIFICATIONS

Model	BCBHR-204
Maximum Capacity (No of tubes x Vol.)	4x750 ml
Temperature Range	-20°C to +40°C
Temperature Accuracy	±1°C
Maximum Speed	21000 rpm
Speed Increment	±20 rpm
Maximum RCF	30642xg
Time Range	0-99 min
Overall Dimension	610x622x360 mm
Program	10 user programs
Control	Microcomputer
Display	LCD
Noise Level	≤60dB(A)
Weight (Net/Gross)	85/105 kg
Power Supply	220V, 60Hz

OPTIONAL ACCESSORIES

Accessory Code	Name	Description	RPM	RCF _{xg}
2301214006	Angle Rotor	12x1.5/2.2ml	21000	30642 _{xg}
2301214007	Angle Rotor	10x5ml	16500	18360 _{xg}
2301214008	Angle Rotor	12x10ml	15000	23120 _{xg}
2301214009	Angle Rotor	6x30ml	15000	23120 _{xg}
2301214010	Angle Rotor	6x50ml	13000	17940 _{xg}
2301214011	Swing Rotor	4x750ml	4000	3500 _{xg}



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
Email: contact@biolabscientific.com | Website: www.biolabscientific.com