



BENCHTOP LOW SPEED CENTRIFUGE BCBL-203

BENCHTOP LOW SPEED CENTRIFUGE BCBL-203

Designed around your applications to provide you competent sample processing and reliable results. Microcomputer programmable with excellent temperature controls and low noise operation maximize your productivity. Highly efficient with low maintenance requirements, it is an ideal separation tool for multiple research applications.

Used in Cell Separation, Precipitation, Sample Processing, Clinical, Cell Culture, Microplate Processing, Biochemistry, medical diagnosis.

Also known as Floor Standing Centrifuge, Laboratory Floor Type Centrifuge, Benchtop Centrifuge, Non Refrigerated High Speed Centrifuge, Laboratory Tabletop Centrifuge.

BCBL-203 BENCHTOP LOW SPEED CENTRIFUGE



Microcomputer controlled programmable operation with touch panel

TFT true-colour LCD wide screen displays set and run conditions for easy monitoring
Brushless DC Motor ensures low maintenance, high efficiency and constant speed of rotation

Store 20 programs in centrifuge memory which are retained even after powering down the centrifuge

Fully stainless steel structure and stainless steel cavity makes the machine safe and more efficient

Acceleration/Deceleration takes around 30 sec to 1 min

Multiple layers of shock absorbers with auto balancing function

System is complemented by multiple new accessories, including tube racks, centrifuge adapters and rotors

Safety features: Self diagnostic, Rotor unbalance detector, Lid protection, over speed protection, over temperature protection

SPECIFICATIONS

Model	BCBL-203
Maximum Capacity (No of tubes x Vol.)	4x250 ml
Maximum Speed	4000 rpm
Maximum RCF	2830×g
Time Range	0-99 h 59 min
Overall Dimension	600mm×540mm×360mm
Program	20 user programs
Control	Microcomputer
Display	LCD
Noise Level	≤65dB(A)
Weight (Net/Gross)	35/42 kg
Power	800 W
Power Supply	220V, 50Hz



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com