



BENCHTOP LOW SPEED CENTRIFUGE BCBL-309

BENCHTOP LOW SPEED CENTRIFUGE BCBL-309

Designed around your applications to provide you competent sample processing and reliable results. Microcomputer programmable with excellent temperature controls and low noise operation maximize your productivity. Highly efficient with low maintenance requirements, it is an ideal separation tool for multiple research applications. Used in Cosmetic Surgery, Moden Beauty Salon.

BCBL-309 BENCHTOP LOW SPEED CENTRIFUGE



Brushless DC Frequency motor with simpler construction, more reliable performance, longer life and quietly running

Smooth in operation, low noise.

Microcomputer control system, digital display in RCF, time and speed.

There are 10 kinds of acceleration and deceleration for your choice.

Automatic electric lid, compact design, super speed and imbalance protection.

The centrifuge body is made of high-quality steel, safe and reliable.

SPECIFICATIONS

Model	BCBL-309
Maximum Capacity (No of tubes x Vol.)	4x20 ml (PRP kit)
Maximum Speed	4000 rpm
Speed Accuracy	±20rpm
Maximum RCF	2720xg
Time Range	0~99min
Noise Level	≤55 dBA
Power Supply	AC 220V/110V 50/60HZ 2A
Overall Dimension	528x370x280mm
Net. Weight	28 kg
Package	carton box



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com