





BENCHTOP LOW SPEED REFRIGERATED CENTRIFUGE BCBLR-203





BENCHTOP LOW SPEED REFRIGERATED CENTRIFUGE BCBLR-203

Engineered to maximize productivity and reliably deliver a wide range of low speed separations. Stainless steel interiors, integrated refrigeration system and advanced temperature controls make it flexible for your evolving applications. Safety features and low noise operation make it an ideal partner for your day to day separations. Used in Cell Separation, Precipitation, Sample Processing, Clinical, Cell Culture, Microplate Processing, Biochemistry, medical diagnosis.

Also known as Floor Standing Centrifuge, Laboratory Floor Type Centrifuge, Floor Type Refrigerated Centrifuge, Benchtop Centrifuge, Laborartory Tabletop Centrifuge.

BCBLR-203 BENCHTOP LOW SPEED REFRIGERATED CENTRIFUGE



Microcomputer controlled programmable operation with push-button operation

TFT true-colour LCD wide screen displays set and run conditions for easy monitoring Brushless DC Motor ensures low maintenance, high efficiency and constant speed of rotation

Store 20 programs in centrifuge memory which are retained even after powering down the centrifuge

Fully stainless steel structure and stainless steel cavity makes the machine safe and more efficient

Triple protective layers of steel bushings

Acceleration/Deceleration takes around 30 sec to 1 min

Multiple layers of shock absorbers with auto balancing function

System is complemented by multiple new accessories, including tube racks, centrifuge adapters and rotors

Safety features: Self diagnostic, Rotor unbalance detector, Lid protection, over speed protection, over temperature protection

SPECIFICATIONS

| Model | BCBLR-203 |
|---------------------------------------|------------------|
| Maximum Capacity (No of tubes x Vol.) | 4x500 ml |
| Temperature Range | -20°C to 40°C |
| Temperature Accuracy | ±1°C |
| Maximum Speed | 8000 rpm |
| Speed Increment | ±50 rpm |
| Maximum RCF | 6460×g |
| Time Range | 0-99 h 59 min |
| Overall Dimension | 630x760x400 mm |
| Program | 20 user programs |
| Control | Microcomputer |
| Display | LCD |
| Noise Level | ≤65dB |
| Weight (Net/Gross) | 110/150 kg |
| Power | 1800 W |
| Power Supply | 220V, 50Hz 10A |

OPTIONAL ACCESSORIES

| Accessory Code | Name | Description | RPM | RCFxg |
|----------------|--------------------------------|--------------|------|--------|
| 2301910006 | Fixed Angle Rotor | 12x10ml | 5500 | 4328xg |
| 2301910007 | Swinging-bucket Rotor | 12x15ml | 5000 | 4500xg |
| 2301910008 | Swinging-bucket Rotor | 24x10ml | 5000 | 4500xg |
| 2301910009 | Swinging-bucket Rotor- Adapter | 4x250ml | 4000 | 3290xg |
| 2301910010 | Swinging-bucket Rotor- Adapter | 8x50ml | 4000 | 3290xg |
| 2301910011 | Swinging-bucket Rotor- Adapter | 24 x15ml | 4000 | 3290xg |
| 2301910012 | Swinging-bucket Rotor- Adapter | 32 x10ml | 4000 | 3290xg |
| 2301910013 | Swinging-bucket Rotor- Adapter | 40 x5ml | 4000 | 3290xg |
| 2301910014 | Swinging-bucket rotor | | | |
| 2301910015 | Swinging-bucket rotor- Buckets | 4x50ml | 5000 | 4600xg |
| 2301910016 | Swinging-bucket rotor- Buckets | 4x100ml | 5000 | 4800xg |
| 2301910017 | Swinging-bucket rotor- Buckets | 8x50ml | 4000 | 2810xg |
| 2301910018 | Swinging-bucket rotor- Buckets | 32 x15ml | 4000 | 2810xg |
| 2301910019 | Swinging-bucket rotor- Buckets | 32 x10ml | 4000 | 2810xg |
| 2301910020 | Swinging-bucket rotor- Buckets | 48x5ml /2ml | 4000 | 2940xg |
| 2301910021 | Swinging-bucket Rotor | 76x5ml /2 ml | 4000 | 3100xg |
| 2301910022 | Swing Micro- Plate Rotor | 2x2x96 holes | 4000 | 2360xg |



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada Email: info@biolabscientific.com | Website: www.biolabscientific.com