



BIOLOGICAL SAFETY CABINET CLASS II BCBS-402

BIOLOGICAL SAFETY CABINET CLASS II BCBS-402

Biolab Biological Safety Cabinet Class II Series is engineered specifically for laboratory operations that require user and product protection. Operates with a negative air pressure for personnel protection and HEPA filtered laminar airflow for product protection. Suitable for microbiological and research applications that do not involve radioactive substances and toxic contaminants.

Used in Cell culturing, Genetics, Microbiological, Research, Cell Biology, Molecular Biology, Plant, Laboratory.
Also known as Class II BSC, Biosafety Cabinet.

BCBS-402 BIOLOGICAL SAFETY CABINET CLASS II



- Time reserve function
- Stainless Steel 304 table for operation
- Digital VFD display for easy monitoring of all parameters
- Emission of 253.7 nm for highly efficient decontamination
- Two-layered marinated toughened glass ($\geq 5\text{mm}$) motorized front window
- Negative air pressure provides personnel protection by constant movement of air in working area
- Remote control operation including front sash movement and fan speed control
- Motored front window with timer function
- Intrinsic sterilization is achieved after activating cabinet for 30 min via UV timing
- Filter Life Indicator: Pressure value displayed to show life utility of main filter
- Foot switch to adjust the height of the front window
- Low noise and high energy efficiency for operational cost savings
- Audio and visual alarm for filter replacement, front window over height and abnormal airflow

SPECIFICATIONS

Model	BCBS-402
Type	Class II, Type B2
Filter	ULPA Filter - Two, 99.9995% efficiency at 0.12 μm , filter life indicator
Inflow Velocity	0.53 \pm 0.025 m/s
Down Flow Velocity	0.33 \pm 0.025 m/s
UV Lamp	30Wx1 UV timer, UV life indicator, emission of 235.7 nanometers for most efficient decontamination
LED Lamp	14Wx2
Illumination	≥ 1000 lux
Waterproof Socket	Two, total load of sockets: 500W
Work Surface Height	750 mm (Size can be customized according to requirements)
Tested Opening	Safety height 200 mm (8")
Max Opening	440 mm
Front Window	Motorized, two layer laminated toughened glass ≥ 6 mm, Anti UV
Airflow System	0% air recirculation, 100% air exhaust
Control System	Microprocessor
Caster	Footmaster Caster
Display	LCD Display: exhaust filter and downflow filter pressure, filter and UV lamp working time, inflow and downflow velocity, filter life, humidity and temperature, system working time etc.
Work Zone Material	304 Stainless steel
Main Body Material	Cold roller steel with anti bacteria powder coating

Visual and Audio Alarm	Abnormal airflow velocity, filter replacement, front window at unsafe height, high filter pressure alarm, abnormal power failure
Standard Accessory	LED lamp 2pcs, UV lamp 1 pc, Base stand Remote control, Foot switch, Drain valve, Waterproof Socket 2 pcs, Exhaust blower, Exhaust duct
Optional Accessory	Water and Gas tap, Electric Height adjustable base stand, Armrest
Noise	≤65dB
Internal Size (WxDxH)	1150x600x660 mm
External Size (WxDxH)	1300x755x2250 mm
Package Size (WxDxH)	1430x1060x1840 mm 930x860x740 mm
Gross Weight	282 kg ; 64 kg
Consumption	1300 W
Power Supply	AC220V 50/60Hz ; 110 60Hz

ACCESSORIES

Accessory Code	Name
6000606013	UV Lampx2

OPTIONAL ACCESSORIES

Accessory Code	Name	External Dimension	Package Size (mm)
2200606006	Infrared Sterilizer	150x95x210 mm	
2200606007	Airflow Tester		
2200606008	Formalin Fumigation Sterilizer		300x200x160 mm
2200606009	Ammonium Hydrogen Carbonate Neutralizer		300x200x160 mm
2200606010	Armrest		
2200606011	Laboratory Chair		
2200606012	Dust Particle Counter		
2200606013	Digital Sound Level Meter		
2200606014	Illumination Meter		
2200606015	Air Flow Anemometer		
2200606016	Protective Garment		
2200606017	Protective Gloves		



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com