



CLIMATIC CHAMBER BCCL-102

CLIMATIC CHAMBER BCCL-102

Our chambers provide excellent temperature and lighting control for regulated growth of plants and other products. Its responsive humidification sensor and energy efficient design make it a preferred choice for a wide range of applications.

Used in Supports plant and insect growth, tissue cultivation, antibiotic cultivation and preservation and other controlled temperature experiments..

Also known as Humidity Chamber, Laboratory Climatic Chamber.

BCCL-102 CLIMATIC CHAMBER



Programmable microcomputer based PID controller with LCD display

Unique air circulation system ensures temperature uniformity

Mirror finished stainless steel inner chamber and cold-rolling steel with static spray plastics exterior

Double door design with built-in tempered glass viewing window

Built in high capacity intelligent humidification system

Automatic water replenishment by external tank

3-side illumination can be adjusted in five steps

Durable refrigeration system with small temperature fluctuation, auto defrosting and multiple layers security

Environment efficient, energy-saving Fluorine-free Refrigerant R134

Timer and over temperature alarm function

SPECIFICATIONS

Model	BCCL-102
Capacity	250 L
Temperature Range	5-50°C (Light off), 10-50°C (Light on)
Temperature Accuracy	±0.5°C
Temperature Uniformity	±2°C
Temperature Fluctuation	±2°C
Temperature Resolution	0.1°C
Temperature Sensor	Pt 100Ω
Illumination Range	0-15000 lux
Timer Range	0-99h
Control Steps	5 Steps
Shelves	2
Load per Shelf	10 kg
Inner Dimension	1000x550x450 mm
Overall Dimension	1550x690x660 mm
Weight (Net/Gross)	155/200 kg
Power	1000 W
Power Supply	220V, 50Hz



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com