



CLIMATIC CHAMBER BCCL-1305

CLIMATIC CHAMBER BCCL-1305

BCCL-1305 CLIMATIC CHAMBER



Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable

Microprocessor controller for temperature and humidity ensures of precise and reliable control

Imported compressor

Independent temperature-limiting alarm system ensures experiments run safely

Printer connector and RS485 connector are options which can connect printer and computer to record the parameters and the variations of temperature

There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement

SPECIFICATIONS

| Model | BCCL-1305 |
|------------------------|--|
| Capacity | 800 L |
| Temperature Range | 5-80°C |
| Display Resolution | 0.1°C |
| Temperature Stability | High $\pm 0.5^{\circ}\text{C}$ Low $\pm 1^{\circ}\text{C}$ |
| Temperature Uniformity | $\pm 2^{\circ}\text{C}$ |
| Humidity Range | 40-85% |
| Power Consumption | 8050 W |
| Ambient Temperature | +5 - 35°C |
| Electrical Requirement | 220 V 50 Hz |
| Interior Dimension | 800Wx590Dx1650H mm |
| Exterior Dimension | 1360Wx890Dx2000H mm |
| Shelves | 4 pcs |



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com