



CLIMATIC CHAMBER BCCL-1310

CLIMATIC CHAMBER BCCL-1310

BCCL-1310 CLIMATIC CHAMBER



Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable

Microprocessor controller for temperature and humidity ensures of precise and reliable control

Imported compressor

Independent temperature-limiting alarm system ensures experiments run safely

Printer connector and RS485 connector are options which can connect printer and computer to record the parameters and the variations of temperature

There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement

SPECIFICATIONS

Model	BCCL-1310
Capacity	800 L
Temperature Range	10-70°C
Display Resolution	0.1°C
Temperature Stability	High $\pm 0.5^{\circ}\text{C}$ Low $\pm 1^{\circ}\text{C}$
Temperature Uniformity	$\pm 2^{\circ}\text{C}$
Humidity Range	40-95%
Power Consumption	8050 W
Ambient Temperature	+5 - 35°C
Electrical Requirement	220 V 50 Hz
Interior Dimension	800Wx590Dx1650H mm
Exterior Dimension	1360Wx890Dx2000H mm
Shelves	4 pcs



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com