



CLIMATIC CHAMBER BCCL-1401

CLIMATIC CHAMBER BCCL-1401

BCCL-1401 CLIMATIC CHAMBER



Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the height between the shelves in the chamber are adjustable

Homogeneity air circulating system

With temperature and humidity sensor

With programmable controller, large LCD screen

R134A refrigerant, With compressor and fan motor

A 25mm validation port on side of the chamber for easy testing operation and temperature validation

Over temperature and temperature deviation alarms

Compressor over-heat and over-load protections, fan motor over-heat and waterlack protections

Independent audible and visible temperature-limiting alarm system ensures experiments run safely

SPECIFICATIONS

Model	BCCL-1401
Capacity	50 L
Temperature Range	RT+10-85°C
Temperature Accuracy	0.1°C
Temperature Stability	±1.0°C
Humidity control range	80-95%RH
Humidity Accuracy	±3%RH
Power Consumption	1450 W
Ambient Temperature	+5 - 35°C
Electrical Requirement	220 V 50 Hz
Interior Dimension	350Wx300Dx500H mm
Exterior Dimension	720Wx620Dx725H mm
Shelves	2 pcs



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com