



CLIMATIC CHAMBER BCCL-1403

CLIMATIC CHAMBER BCCL-1403

BCCL-1403 CLIMATIC CHAMBER



Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the height between the shelves in the chamber are adjustable

Homogeneity air circulating system

With temperature and humidity sensor

With programmable controller, large LCD screen

R134A refrigerant, With compressor and fan motor

A 25mm validation port on side of the chamber for easy testing operation and temperature validation

Over temperature and temperature deviation alarms

Compressor over-heat and over-load protections, fan motor over-heat and waterlock protections

Independent audible and visible temperature-limiting alarm system ensures experiments run safely

SPECIFICATIONS

Model	BCCL-1403
Capacity	250 L
Temperature Range	RT+10-85°C
Temperature Accuracy	0.1°C
Temperature Stability	±1.0°C
Humidity control range	80-95%RH
Humidity Accuracy	±3%RH
Power Consumption	2050 W
Ambient Temperature	+5 - 35°C
Electrical Requirement	220 V 50 Hz
Interior Dimension	600Wx500Dx820H mm
Exterior Dimension	750Wx900Dx1580H mm
Shelves	2 pcs



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com