





FLOOR TYPE LOW SPEED REFRIGERATED CENTRIFUGE BCFLR-203





FLOOR TYPE LOW SPEED REFRIGERATED CENTRIFUGE BCFLR-203

Engineered to maximize productivity and reliably deliver a wide range of low speed separations. Stainless steel interiors, integrated refrigeration system and advanced temperature controls make it flexible for your evolving applications. Safety features and low noise operation make it an ideal partner for your day to day separations. Used in Cell Separation, Precipitation, Sample Processing, Clinical, Cell Culture, Microplate Processing, Biochemistry, medical diagnosis.

Also known as Floor Standing Centrifuge, Laboratory Floor Type Centrifuge, Floor Type Refrigerated Centrifuge, Benchtop Centrifuge, Laborartory Tabletop Centrifuge.

BCFLR-203 FLOOR TYPE LOW SPEED REFRIGERATED CENTRIFUGE



Microcomputer controlled programmable operation with push-button operation

TFT true-colour LCD wide screen displays set and run conditions for easy monitoring Brushless DC Motor ensures low maintenance, high efficiency and constant speed of rotation

Store 20 programs in centrifuge memory which are retained even after powering down the centrifuge

Fully stainless steel structure and stainless steel cavity makes the machine safe and more efficient

Triple protective layers of steel bushings

Acceleration/Deceleration takes around 30 sec to 1 min

Multiple layers of shock absorbers with auto balancing function

System is complemented by multiple new accessories, including tube racks, centrifuge adapters and rotors

Safety features: Self diagnostic, Rotor unbalance detector, Lid protection, Over speed protection, Over temperature protection

SPECIFICATIONS

Model	BCFLR-203	
Maximum Capacity 4×750ml	Swing bucket rotor 4x750 ml	
Temperature Range	-20°C to 40°C	
Temperature Accuracy	±1°C	
Maximum Speed	8000 rpm	
Speed Increment	±50 rpm	
Maximum RCF	5940xg	
Time Range	0-99 h 59 min	
Overall Dimension	580mm×740mm×800mm	
Program	20 user programs	
Control	Microcomputer	
Display	LCD	
Noise Level	≤65dB(A)	
Weight (Net/Gross)	150/210 kg	
Power	2000 W	
Power Supply	220V, 60Hz	

OPTIONAL ACCESSORIES

Accessory Code	Name	Description	RPM	RCFxg
2301906006	Fixed Angle Rotor	12x10ml	5500	3580xg
2301906007	Swinging-bucket Rotor	4x750ml	4000	3500xg
2301906008	Swinging-bucket Rotor	4x500ml round	4000	3780xg
2301906009	Swinging-bucket Rotor- Adapter	4x250/300ml	4000	3780xg
2301906010	Swinging-bucket Rotor- Adapter	4x100ml	4000	3780xg
2301906011	Swinging-bucket Rotor- Adapter	12x50ml	4000	3780xg
2301906012	Swinging-bucket Rotor- Adapter	32 x15ml	4000	3780xg
2301906013	Swinging-bucket Rotor- Adapter	72x5ml	4000	3780xg
2301906014	Swinging-bucket Rotor	148x5 ml/2ml	4000	2900xg
2301906015	Swinging-bucket Rotor	76x5 ml/2ml	4000	3100xg
2301906016	Swinging-bucket Rotor	16x15ml	5000	4500xg
2301906017	Swinging-bucket Rotor- Buckets	4x100ml	5000	4800xg
2301906018	Swinging-bucket Rotor- Buckets	8x50ml	4000	2810xg
2301906019	Swinging-bucket Rotor- Buckets	24x10ml	4000	2810xg
2301906020	Swinging-bucket Rotor- Buckets	32x15ml	4000	2810xg
2301906021	Swinging-bucket Rotor- Buckets	32x10ml	4000	2810xg
2301906022	Swinging-bucket Rotor- Buckets	48x5ml/2ml	4000	2950xg
2301906023	Swing Micro-Plate Rotor	2x2x96 2x2x96 places	4000	2360xg



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada Email: info@biolabscientific.com | Website: www.biolabscientific.com