



## LOW TEMPERATURE CIRCULATOR BCLT-2101

# LOW TEMPERATURE CIRCULATOR BCLT-2101

## BCLT-2101 LOW TEMPERATURE CIRCULATOR



P.I.D temperature controller provides accurate and reliable temperature control  
Large LCD display screen and interface provides for user-friendly operation  
Preset On/Off function  
Independent circulating pump switch for easy starting/stopping the cycle  
Easy to set Adjustable Timer. (1 minute to 5,999 minutes)  
Maintenance-free operation with easy to clean surface  
Both heater and bath chamber are made of corrosion-resistant stainless steel  
No angle in bath chamber, easy to clean. Uniquely designed heating method can up to 80 °C  
Programming setting function with 7 periods and 9 steps for each period, which means. There are 63 programmable steps in total

## SPECIFICATIONS

Model	BCLT-2101
Capacity	5 L
Temperature range	-20 - 20°C
Temperature accuracy	±2°C
Cooling capacity at 10°C	530 W
Refrigerant	R404A
Security features	Delay, leakage, overcurrent, overvoltage
Total power	550 W
Power requirements	AC 220 V / 50 HZ
Pump power	30
Pump flow max.	6 L / min
Maximum head	9 m
Inlet/Outlet pipe diameter	Φ10 mm
Weight	32
Liquid storage	3.5
Noise level	≤45
Dimension	210Wx410Dx511H mm



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)