



LOW TEMPERATURE CIRCULATOR BCLT-2102

LOW TEMPERATURE CIRCULATOR BCLT-2102

BCLT-2102 LOW TEMPERATURE CIRCULATOR



P.I.D temperature controller provides accurate and reliable temperature control
Large LCD display screen and interface provides for user-friendly operation
Preset On/Off function
Independent circulating pump switch for easy starting/stopping the cycle
Easy to set Adjustable Timer. (1 minute to 5,999 minutes)
Maintenance-free operation with easy to clean surface
Both heater and bath chamber are made of corrosion-resistant stainless steel
No angle in bath chamber, easy to clean. Uniquely designed heating method can up to 80 °C
Programming setting function with 7 periods and 9 steps for each period, which means. There are 63 programmable steps in total

SPECIFICATIONS

Model	BCLT-2102
Capacity	8 L
Temperature range	-20 - 20°C
Temperature accuracy	±2°C
Cooling capacity at 10°C	600 W
Refrigerant	R404A
Security features	Delay, leakage, overcurrent, overvoltage
Total power	600 W
Power requirements	AC 220 V / 50 HZ
Pump power	30
Pump flow max.	6 L / min
Maximum head	9 m
Inlet/Outlet pipe diameter	Φ10 mm
Weight	41
Liquid storage	5.2
Noise level	≤45
Dimension	310Wx445Dx570H mm



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com