



## LOW TEMPERATURE CIRCULATOR BCLT-2103

## LOW TEMPERATURE CIRCULATOR BCLT-2103

### BCLT-2103 LOW TEMPERATURE CIRCULATOR



- P.I.D temperature controller provides accurate and reliable temperature control
- Large LCD display screen and interface provides for user-friendly operation
- Preset On/Off function
- Independent circulating pump switch for easy starting/stopping the cycle
- Easy to set Adjustable Timer. (1 minute to 5,999 minutes)
- Maintenance-free operation with easy to clean surface
- Both heater and bath chamber are made of corrosion-resistant stainless steel
- No angle in bath chamber, easy to clean. Uniquely designed heating method can up to 80 °C
- Programming setting function with 7 periods and 9 steps for each period, which means. There are 63 programmable steps in total

## SPECIFICATIONS

Model	BCLT-2103
Capacity	15.5 L
Temperature range	-20 - 20°C
Temperature accuracy	±2°C
Cooling capacity at 10°C	1500 W
Refrigerant	R410A
Security features	Delay, leakage, overcurrent, overvoltage
Total power	1300 W
Power requirements	AC 220 V / 50 HZ
Pump power	60
Pump flow max.	17 L / min
Maximum head	15 m
Inlet/Outlet pipe diameter	Φ12 mm
Weight	60
Liquid storage	13
Noise level	≤55
Dimension	400Wx500Dx739H mm



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)