



## LOW TEMPERATURE CIRCULATOR BCLT-2105

# LOW TEMPERATURE CIRCULATOR BCLT-2105

## BCLT-2105 LOW TEMPERATURE CIRCULATOR



P.I.D temperature controller provides accurate and reliable temperature control  
Large LCD display screen and interface provides for user-friendly operation  
Preset On/Off function  
Independent circulating pump switch for easy starting/stopping the cycle  
Easy to set Adjustable Timer. (1 minute to 5,999 minutes)  
Maintenance-free operation with easy to clean surface  
Both heater and bath chamber are made of corrosion-resistant stainless steel  
No angle in bath chamber, easy to clean. Uniquely designed heating method can up to 80 °C  
Programming setting function with 7 periods and 9 steps for each period, which means. There are 63 programmable steps in total

## SPECIFICATIONS

Model	BCLT-2105
Capacity	62 L
Temperature range	-20 - 20°C
Temperature accuracy	±2°C
Cooling capacity at 10°C	4000 W
Refrigerant	R410A
Security features	Delay, leakage, overcurrent, overvoltage
Total power	2400 W
Power requirements	AC 220 V / 50 HZ
Pump power	550
Pump flow max.	30 L / min
Maximum head	25 m
Inlet/Outlet pipe diameter	Φ12 mm
Weight	126
Liquid storage	52
Noise level	≤75
Dimension	560Wx845Dx850H mm



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)