



LOW TEMPERATURE CIRCULATOR BCLT-2204

LOW TEMPERATURE CIRCULATOR BCLT-2204

BCLT-2204 LOW TEMPERATURE CIRCULATOR



P.I.D temperature controller provides accurate and reliable temperature control
Large LCD display screen and interface provides for user-friendly operation
Preset On/Off function
Independent circulating pump switch for easy starting/stopping the cycle
Easy to set Adjustable Timer. (1 minute to 5,999 minutes)
Maintenance-free operation with easy to clean surface
Both heater and bath chamber are made of corrosion-resistant stainless steel
No angle in bath chamber, easy to clean. Uniquely designed heating method can up to 80 °C
Programming setting function with 7 periods and 9 steps for each period, which means. There are 63 programmable steps in total

SPECIFICATIONS

Model	BCLT-2204
Capacity	30 L
Temperature range	-20 - 80°C
Temperature accuracy	±0.5°C
Cooling capacity at 10°C	2500 W
Refrigerant	R410A
Security features	Delay, leakage, overcurrent, overvoltage
Total power	3000 W
Power requirements	AC 220 V / 50 HZ
Pump power	60
Pump flow max.	17 L / min
Maximum head	15 m
Inlet/Outlet pipe diameter	Φ12 mm
Weight	76
Liquid storage	25
Noise level	≤65
Dimension	450Wx600Dx821H mm



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com