



LOW TEMPERATURE CIRCULATOR BCLT-2601

LOW TEMPERATURE CIRCULATOR BCLT-2601

BCLT-2601 LOW TEMPERATURE CIRCULATOR



Microprocessor temperature controller with LCD screen ensures precise and reliable control, easy to operate

No angle in bath chamber, easy to clean

Programming setting function with 7 periods and 9 steps for each period, which means there are 63 programmable steps in total

R134a refrigerant

With interface to external water bath

Easy to set adjustable timer. (1 minute to 5,999 minutes)

Maintenance-free operation with easy to clean surface

Both heater and bath chamber are made of corrosion-resistant stainless steel

Drain valve makes emptying of bath water fast and easy for cleaning and moving

SPECIFICATIONS

| | |
|---------------------------|----------------|
| Model | BCLT-2601 |
| Capacity | 4.5 L |
| Temperature range | -10 - 100°C |
| Precision | ±0.2 |
| Liquid tank opening/depth | 150x160/150 mm |
| Power requirements | AC 220 V 50 HZ |
| Pump | 8 L/min |
| Power Consumption | 2300 W |



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com