



LOW TEMPERATURE CIRCULATOR BCLT-502

LOW TEMPERATURE CIRCULATOR BCLT-502

We offer you robust circulators equipped with microprocessor controller for high heating and cooling experiments. Fitted with adjustable casters, corrosion resistant interior and exterior, these circulators are a perfect fit for any environment.

Used in Enzyme reactions, Immunoassay, Incubation, Laboratory, Research, Medical, Pharmaceuticals.

Also known as Laboratory water bath.

BCLT-502 LOW TEMPERATURE CIRCULATOR



- PID controller offers precise temperature control and uniformity
- Corrosion resistant inner and outer chamber made of stainless steel
- Dual LED screen displays temperature and time
- Protection against compressor overload, high/low voltage and current
- Convenient and reliable operation
- Equipped with caster for easy installation

SPECIFICATIONS

Model	BCLT-502
Capacity	12 L
Temperature Range	-40°C to 100°C
Temperature Resolution	±0.1°C
Top Opening	170x110 mm
Inner Dimension (WxDxH)	240x300x200 mm
Outer Dimension (WxDxH)	450x570x850 mm
Power	360 W



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com