



## CO2 INCUBATOR WATER JACKETED BCWJ-8503

# CO2 INCUBATOR WATER JACKETED BCWJ-8503

## BCWJ-8503 CO2 INCUBATOR WATER JACKETED



Faster CO2 concentration Restoration Speed

Infrared sensor can keep CO2 concentration stability and uniformity when door open frequently

Polished stainless-steel chamber, and the space between the shelves in the chamber is adjustable

Microorganism filter at inlet provides 99.99% filtration of bacteria and dust ( $\Phi < 0.3\mu\text{m}$ ) and supplies pure CO2 into the incubator

Door temperature controller prevents dewfall on glass door of incubator effectively

Independent audible and visible temperature-limiting alarm system ensures experiments run safely

Alarm function for temperature difference, CO2 over concentration and concentration difference, door open time, UV working status

Auto-controller of fan speed to prevent damage to the samples

UV light system for periodic sterilization of chamber

PID controller with LCD screen ensures precise and reliable control

Two-layer stacking available

## SPECIFICATIONS

Model	BCWJ-8503
Capacity	150 L
Electrical Requirement	220 V 50 Hz
Power Consumption	950 W
Temperature Range	RT+5 - 50°C
Ambient Temperature	+5 - 30°C
Temperature Stability	±0.2°C
CO2 Range	0 - 20% V/V
CO2 Control Resolution	±0.1%(IR sensor)
CO2 Recovery	(Door open 30s,recovery to 5%) ≤ 3min
Temperature Recovery	(Door open 30s,recovery to 37°C ) ≤ 8min
Humidity Method	Natural vaporization ≥ 90%
Interior Dimension	500Wx500Dx650H mm
Exterior Dimension	650Wx615Dx914H mm
Shelves	3 pcs
Sterilization method	UV Sterilizer



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)