



MINI DRY BATH INCUBATOR BDMI-101

MINI DRY BATH INCUBATOR BDMI-101

Biolab Mini Dry bath incubator features precise temperature control resolution in a compact design to give you reproducible results. This microprocessor controlled device offers you flexibility to accommodate a variety of interchangeable heating blocks for your versatile applications.

Used in Immunoassays, Melting points, Enzyme reactions, Boiling points, Incubation, Activation of cultures, Laboratory procedures..

Also known as Digital Dry Bath Incubator, Heating block, Laboratory Dry Bath Incubator.

BDMI-101 MINI DRY BATH INCUBATOR



- Microprocessor controlled incubation temperature and time
- Compact design with stable operation
- Rapid heat up, uniform heating, high stability, low energy consumption and noise
- Simultaneous display of set temperature and time
- Built in temperature calibration function
- Aluminium blocks ensures even heat distribution, eliminating the possibility of heater burnout
- Custom blocks available to meet experimental requirements
- Easy cleaning, replacement and disinfection of metal blocks
- Automatic fault detection and buzzer alarm function
- Audio alarm indicates program completion
- Over temperature protection device

SPECIFICATIONS

Model	BDMI-101
Temperature Range	RT+5 °C-100 °C
Temp. Setting Range	0 °C~100 °C
Temp. Stability@100°C	±0.5 °C
Temp. Stability@40°C	±0.3 °C
Block Temp. Uniformity	±0.3 °C
Temp. Display Accuracy	0.1 °C
Heating Speed	≤15 min (20 °C to 100 °C)
Cooling Speed	natural cooling
Heating Cover	No
Time Range	1 sec~999 sec or 1 min~999 min
Voltage	DC24V adapter
Power	60 W
Dimension	W.110 x D.156 x H.103mm
Net Weight	1 kgs



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
Email: contact@biolabscientific.com | Website: www.biolabscientific.com