



MEDIUM WATER PURIFICATION SYSTEM BDPS-401

MEDIUM WATER PURIFICATION SYSTEM BDPS-401

This medium series is an excellent choice of high-performance water purifying system. The self-flushing of the reverse osmosis membrane, extend the life of RO membrane. These systems are Level II password protected for all the parameters setting, and forbid any unauthorized settings change also It has multiple alarm functions.

Used in Laboratory, Manufacturing, Reefkeeping, Aquarium, Laboratory, Research.

Also known as Laboratory Ultrapure water system.

BDPS-401 MEDIUM WATER PURIFICATION SYSTEM



Automatic microcomputer controlling system, multi-menu operating, real-time animation mode display.

Super-large LCD (Resolution:240×128, dimension:106×57mm) display, display the system running state and various parameters intuitively.

3 way on-line sensor, detect the quality of feed water, RO water, or ultrapure water respectively.

System sterilization procedure, achieve the disinfection of ultrapure water's pipeline.

System circulation function, circulate water when the system stops working, to keep water quality.

Self-flushing of the reverse osmosis membrane, extend the life of RO membrane.

Multiple alarm functions: such as no water, full water, disqualification of feed water, RO water, deionized water or ultrapure water, cartridges' life-span ends.

The cartridge's life-span can be set, the time used and left can be displayed, replacing auto-reminding, avoiding the decline of water quality.

Level II password, protect all the parameters setting, and prohibit any unauthorized settings change.

Water dispensing function-timing and quality (Time range:1-99min, water quality range:0.1-18.2MΩ.cm).

RS 232/USB communication port(optional), at least store 1 years' water quality data.

Different external tanks (optional) to meet every need and assure ample water-supply.

Human engineering design, molding process, high-strength, streamline plastic shell.

Pretreatment cartridges, RO module, ultrapure cartridges, all designed to modularization independently. Easy to maintenance and replacement.

Pipeline and fast-plug adaptor with NSF authorization, assure high quality ultrapure water.

KDF pretreating cartridge, replace the ordinary active carbon, prolong the life-span to 12 months, reduce the running cost.

DOW's RO membrane, ensure stable operation and high desalinization rate.

4 in 1 ultrapure cartridges (also can be divided to 4 independent cartridge), with DOW's nuclear-grade polishing resin, ensure ultrapure water's quality up to 18.2 MΩ.cm, with the lowest TOC dissolution.

Double wavelength (185&254nm) ultraviolet lamp module, restrain bacteria's increase and reduce TOC.

MWCO 5000D ultrafiltration module, effectively eliminate endotoxin precise cell cultivating and IVF.

(0.45±0.1)μm double layer PES terminal disinfection filter, assure the quality absolutely axenic.

SPECIFICATIONS

Model	BDPS-401
Feed Water Requirements*	
Water Inlet	RO water, Distilled water, Deionized water
Temperature	5-45°C
Pressure	1 atm*
Flow Procedure**	AC+DI+TF
Bacteria	<0.1 cfu/ml
Output(25°C)****	Utmost up to 2.0 L/min (less output with UF cartridge)
Pure water outlet	Deionized water and Ultrapure water
DimensionLxWxH	500x360x540 mm
Weight	20 kg
Standard configuration	Main body (Including 1 set of cartridges)+ accessory bag
Power Consumption (W)	120 W
Power Supply	AC110-220 V, 50/60 Hz
Note	*The feed water quality will influence the pure water's quality and cartridges life-span. ** AC:active carbon,DI:ion exchange,UV:ultraviolet,UF:ultrafiltration,TF:terminal microfiltration. ***Value of number will be influenced by feed water quality. ****The output will decrease with terminal filter or UF cartridge.
Deionized water quality	
Resistivity	>5 MΩ.cm
Ultrapure Water Quality	
Resistivity(25°C)	18.2 MΩ.cm
Heavy Metal Ion	<0.1 ppb
TOC***	<10 ppb
Particle (>0.2µm)	<1/ml



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com