



MUFFLE BOX FURNACE BFMF-1200-40

MUFFLE BOX FURNACE BFMF-1200-40

Designed for minimum space requirements, our muffle furnaces work effortlessly at high temperatures and give reliable results. Equipped with electronic controller and memory to store different programs, it makes the operation user friendly. Chambers are crafted for heavy duty operation and minimize heat loss.

BFMF-1200-40 MUFFLE BOX FURNACE

SPECIFICATIONS

Model	BFMF-1200-40
Capacity	40 L
Maximum Temperature	1200°C
Working Temperature	1200°C
Control Unit	B2
Controller Description	5x20 LCD / 4 Steps 2 Prog
Software Options	B2, E4, U8, S16
Control Accuracy	±1°C
Front Face Insulation Material	Ceramic Fire Brick
Door Insulation Material	Ceramic Fibre Board
Housing Material	Steel Sheet
Housing Coating	Epoxy Powder Coating
Chimney	Standard
Heating Element Protection	Quartz Tube
Lockable Door Handle	Sideways
Inner Insulation Material	Insulating Fire Brick
Heating Element Placement	Embedded into Brick Walls
Thermocouple Type	K Type
Heating Element Type	Fe-Cr-Al
Inner Dimension (WxDxH)	300x300x445mm
Outer Dimension (WxDxH)	630x785x840mm
Gross Dimensions (WxDxH)	690x1000x845mm
Net Weight	112 Kg
Gross Weight	136 Kg
Power	7500 W
Maximum Current	3x11.4 A
Electrical Connection	3 Phase
Power Supply	221V / 50Hz



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com