



## -40°C UPRIGHT FREEZER BFUR-40-303

## -40°C UPRIGHT FREEZER BFUR-40-303

Equipped with precise temperature controls, rugged interiors and safety features, our freezers provide you with the most dependable performance with low maintenance. A perfect partner for your multi cold storage purposes in a contemporary lab set up. Microprocessor based temperature controls provide outstanding temperature uniformity with high quality compressor for energy efficiency.

Used in Routine Cold Storage, Laboratories, Biologicals, Pharmaceuticals, Clinical, Research.

Also known as Laboratory ULT freezer, ULT Freezer, Ultra-low Freezer.

## BFUR-40-303 -40°C UPRIGHT FREEZER



LED digital display and increment at 0.1°C

Permanently lubricated cooling fan for safety and longevity

Independent inner door to avoid more cooling leaking out, and provide more stable inside temperature performance

High density CFC-Free urethane foam insulation

Build-in lock with safety

Lockable caster design

Chemically stable, CFC -free, commercially available and environmentally safe refrigerant

Optimized refrigeration system designed to maximize cooling effect and temperature uniformity

Visible and Audible alarm

Corrosion proof cabinet interior design

Power failure protect: the device would be attack by the high current when all devices restart simultaneously, the start-delay function would protect device from the damage

## SPECIFICATIONS

Model	BFUR-40-303
Capacity	278 L
Temperature Range	-30°C to -40°C
Ambient Temperature	10°C ~ +32°C
Defrosting	Manual
Cooling Type	Direct Cooling
Insulation Material	PURF
Refrigerant	R290
Internal Dimension	480x415x1460 mm
Overall Dimension	659x600x1694 mm
Package Size	710x650x1800 mm
Drawers/Shelves	Drawers
Interior	Color sprayed steel
Exterior	Color sprayed steel
Controller	Microprocessor, Digital display
Sensor	NTC
Compressor Brand/QTY	CUBIGEL/1
Condenser	Inside foaming
Noise Level	50 db

Alarm	High/low temperature, Sensor malfunction, Temperature controller malfunction, Door ajar
Standard Accessories	Foot, Castor, Inner door-7drawers
Optional Accessories	USB data logging, Temperature recorder
Weight (Net/Gross)	110/120 kg
Rated Power	185 W
Power Consumption ( Kwh/24hrs )	1.5
Rated Current A	1.5 A
Power Supply	220 V, 50 Hz



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)