



COOLED INCUBATOR BICL-202

COOLED INCUBATOR BICL-202

An energy efficient remedy for storing and cooling samples. Absolutely reliable circulation system with PID temperature controller provides optimum storage conditions for your products.

Used in Germination experiments, Biochemical analysis, Cold storage purposes, Incubation, drying, Low temperature applications..

Also known as Refrigerated Incubator, Laboratory Cooled Incubator.

BICL-202 COOLED INCUBATOR

PID intelligent programmable temperature control system

Forced air convection circulation system ensures temperature uniformity

RS232 interface

Stainless Steel SUS304 inner bag and cold rolling plate powder spray exterior

Freon-free polyurethane foaming insulation reduces energy consumption and improves insulation

Internal silica gel soft plugs make sure the temperature inside the incubator is maintained evenly

Test hole of 45mm equipped on left and right side

Environment efficient, energy-saving CFC-free refrigerant R134a and EBM condenser

Over temperature protection function

Audio alarm for power failure and door ajar

Automatic start and stop function with self-recovery function

SPECIFICATIONS

Model	BICL-202
Capacity	150 L
Temperature Range	-10-65°C
Ambient Temperature	5°C ~ 35°C
Temperature Accuracy	± 0.1°C (45°C)
Temperature Fluctuation	±1°C
Temperature Uniformity	±1°C (45°C)
Temperature Resolution	±0.1°C
Timer Range	0-999999 min
Internal Dimension	500Wx450Dx670H mm
Exterior Dimension	625Wx657Dx1270H mm
Shelves	3
Weight	96.5/105 kg
Cooling Power	175 W
Power	750 W
Power Supply	220V 50 / 60Hz



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com