



COOLED INCUBATOR BICL-7906

COOLED INCUBATOR BICL-7906

BICL-7906 COOLED INCUBATOR



304 stainless steel, mirror polishing processing, easy to clean and maintain
PID controller with over temperature alarm and timing function ensures precise and reliable control, also guarantee an excellent control by microprocessor and the limited number of setting keys ensures an extremely simple and intuitive operability
The inner lamp for observation of the samples is standard supplied
3 fan speed meets all requirements of different experiments
Famous brand compressor with refrigerant R134a

SPECIFICATIONS

Model	BICL-7906
Capacity	248 L
Temperature Range	0 - 60°C
Display Resolution	0.1°C
Temperature Stability	HIGH $\pm 0.5^{\circ}\text{C}$ LOW $\pm 1.0^{\circ}\text{C}$
Temperature Uniformity	$\pm 1.5^{\circ}\text{C}$
Electrical Requirement	220 V 50 Hz
Ambient Temperature	+5°C - 30°C
Power Consumption	600 W
Interior Dimension	540Wx460Dx1000H mm
Exterior Dimension	637Wx662Dx1590H mm
Shelves	3 pcs
Timing Range	0~5999 min
Display	LCD



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com