



COOLED INCUBATOR BICL-7910

COOLED INCUBATOR BICL-7910

BICL-7910 COOLED INCUBATOR



304 stainless steel, mirror polishing processing, easy to clean and maintain
PID controller with over temperature alarm and timing function ensures precise and reliable control, also guarantee an excellent control by microprocessor and the limited number of setting keys ensures an extremely simple and intuitive operability
The inner lamp for observation of the samples is standard supplied
3 fan speed meets all requirements of different experiments
Famous brand compressor with refrigerant R134a

SPECIFICATIONS

Model	BICL-7910
Capacity	1500 L
Temperature Range	0 - 60°C
Display Resolution	0.1°C
Temperature Stability	HIGH $\pm 0.5^{\circ}\text{C}$ LOW $\pm 1.0^{\circ}\text{C}$
Temperature Uniformity	$\pm 2.5^{\circ}\text{C}$
Electrical Requirement	380 V 50 Hz
Ambient Temperature	+5°C - 30°C
Power Consumption	5000 W
Interior Dimension	105Wx590Dx1650H mm
Exterior Dimension	2110Wx890Dx2050H mm
Shelves	3 pcs
Timing Range	0~5999 min
Display	LCD



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com