



COOLED INCUBATOR BICL-8105

COOLED INCUBATOR BICL-8105

BICL-8105 COOLED INCUBATOR



Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable

Latest PID controller

R134a refrigerant, imported compressor

Independent temperature-limiting alarm system ensures experiments run safely

Printer connector and RS485 connector are options which can connect printer and computer to record the parameters and the variations of temperature

There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement

SPECIFICATIONS

Model	BICL-8105
Capacity	500 L
Temperature Range	-10°C - 65°C
Display Resolution	0.1°C
Temperature Stability	HIGH $\pm 0.5^{\circ}\text{C}$ LOW $\pm 1.0^{\circ}\text{C}$
Electrical Requirement	220 V 50 Hz
Ambient Temperature	+5°C - 35°C
Power Consumption	2250 W
Interior Dimension	670Wx720Dx1020H mm
Exterior Dimension	850Wx1100Dx1930H mm
Shelves	3 pcs
Timing Range	0~9999 min



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com