





## GENERAL PURPOSE INCUBATOR BIGP-7704





## **GENERAL PURPOSE INCUBATOR BIGP-7704**

## **BIGP-7704 GENERAL PURPOSE INCUBATOR**



Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the sace between the shelves in the chamber is adjustable

Auto-controller of fan speed to prevent damage to the samples

Large LCD screen to display more data at same time

Self-check function easy to identify problems

Over temperature and temperature difference alarms

There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement

Programmable controller: 7 periods 63 steps, 0  $^{\sim}$  5999mins for each periods, fan speed 0 to 100% adjustable

Independent audible and visible temperature-limiting alarm system ensures experiments run safely

RS485 connector can connect computer and printer to record the parameters and the variations of temperature

## **SPECIFICATIONS**

Model	BIGP-7704
Capacity	243 L
Electrical requirement	220 V 50 Hz
Controller	LCD Programmable controller
Temperature Range	RT+5°C - 80°C
Display Resolution	0.1°C
Temperature Stability	±0.2°C
Ambient Temperature	+5 - 35°C
Power Consumption	600 W
Interior Dimension	600Wx450Dx900H mm
Exterior Dimension	755Wx785Dx1130H mm
Shelves	2 pcs
Timing Range	0~5999 min



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada Email: info@biolabscientific.com | Website: www.biolabscientific.com