



## GENERAL PURPOSE INCUBATOR BIGP-7705

# GENERAL PURPOSE INCUBATOR BIGP-7705

## BIGP-7705 GENERAL PURPOSE INCUBATOR



Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable

Auto-controller of fan speed to prevent damage to the samples

Large LCD screen to display more data at same time

Self-check function easy to identify problems

Over temperature and temperature difference alarms

There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement

Programmable controller: 7 periods 63 steps, 0 ~ 5999mins for each periods, fan speed 0 to 100% adjustable

Independent audible and visible temperature-limiting alarm system ensures experiments run safely

RS485 connector can connect computer and printer to record the parameters and the variations of temperature

## SPECIFICATIONS

Model	BIGP-7705
Capacity	408 L
Electrical requirement	220 V 50 Hz
Controller	LCD Programmable controller
Temperature Range	RT+5°C - 80°C
Display Resolution	0.1°C
Temperature Stability	±0.2°C
Ambient Temperature	+5 - 35°C
Power Consumption	1200 W
Interior Dimension	1000Wx510Dx800H mm
Exterior Dimension	1140Wx850Dx1080H mm
Shelves	2 pcs
Timing Range	0~5999 min



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)