



LABORATORY WATER PURIFICATION SYSTEM BLPS-802

LABORATORY WATER PURIFICATION SYSTEM BLPS-802

Laboratory water purification system uses double stage reverse osmosis technology. It produces double stage RO water, Deionised, EDI and ultrapure water. These systems have 3 way on-line water quality sensor, multiple alarm with unique design and it has easy-to-replace cartridges pack unit.

Used in Laboratory, Manufacturing, Reefkeeping, Aquarium, Laboratory, Research.

Also known as Laboratory Ultrapure water system.

BLPS-802 LABORATORY WATER PURIFICATION SYSTEM



With 5.0 inch touch screen system

3 way water quality sensor

2 way flow sensor for quantified dispensing
single stage RO system

2 pump and Ionpure EDI module

With tap water inlet

The largest capacity is 240 liters per day.

It can produce deionized water and ultrapure water.

SPECIFICATIONS

Model	BLPS-802
Output(25°C)	10 liters/hour
Pure water outlet	2: deionized water, ultrapure water
Resistivity	18.2 MΩcm
TOC	<3ppb
Bacteria	<0.1cfu/ml
Particle	<1/ml
Endotoxin	< 0.001Eu/ml
Silicone rejection rate	>99.9%
Dimension	500x360x540mm
Weight	20Kg
Power	120V



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com