



HAZE METER BMET-1205

HAZE METER BMET-1205

The amount of light that is diffused or scattered through the transparent material is measure by the Haze meter.

BMET-1205 HAZE METER



Double standard ISO & ASTM
Easy to operate, faster and more accurate measurement
Dynamic measurement
With compensation port, so that the measurement data more accurate
Easy to measure and widely applicable to samples
Quality control software

SPECIFICATIONS

Model	BMET-1205
Optical Geometry	Transmittance:O/D Parallel light illumination, diffuse reflection reception
Features	Photoelectric integration, No compensation port
Standards compliant	ASTM D1003/1044,GB/T 2410,JJF 1303-2011,CIE 15.2,JIS K7105,JIS K7361,JIS K 7136
Integrating Sphere Size	Φ 40mm
Illuminant	D65,A,C
Spectral mode	/
Sensor	The PD array detector, satisfies CIE V(λ)2 degree visual response
Measurement Wavelength range	/
Wavelength Pitch	/
Semi-bandwidth	/
Measuring range of transmittance	0~100%
Measurement Aperture	Φ20mm/Φ15mm/Φ8mm/Φ4mm(Select a single diameter)
Sample thickness	less than 170 mm
color space	/
Color Difference Formula	/
Other Colorimetric data	Haze(ASTM D1003/1044),Transmittance T(ASTM)
Observer	2°
Displayed Data	Pass/fail result
Measurement Time	About 1.5s
Measurement accuracy	0.1
Repeatability	Φ20mm,within 0.1 (After the instrument is preheated and calibrated, the standard deviation between the standard haze tablet and the reference value is tested at an interval of 5s.)
Inter-instrument agreement	Φ20mm,with 0.4 (After the instrument is warmed up and corrected, the standard deviation of the haze standard Haze film and the reference value is tested at an interval of 5s.)
Operating Environment	0~40°C (32~104°F)
Storage Environment	-20~50°C (-4~122°F)
Battery Performance	DC 24V, 3A power adapter
Lamp life	5 years, more than 30000000 times measurement

Display	7 inch TFT capacity, Touchscreen display
Interface	USB, printing port
Data Storage	Standard 1000 pcs,sample 10000 pcs
Language	Chinese, English, traditional Chinese
Standard Accessories	Power Adapter, User Guide,Quality Management Software (download from the official website),USB cable,0% calibration box, measuring caliber
Optional Accessory	Mini-printer,Test fixture, standard haze sheet, foot switch
Dimension	290x211x511 mm
Weight	About 7.6 kg



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com