

# PRODUCT CATALOG



## PH/ION METER BMET-503





#### PH/ION METER BMET-503

An ion meter is a device which with the aid of electrochemical activity of ion electrodes measures the concentration of ions in a solution. It works by the means of selective ion electrodes and measuring ion activity capability of sensitive membrane of a measuring devices. A sensor electrode and a reference electrode are used to measure the ion concentration in a solution.

## **BMET-503 PH/ION METER**



## **SPECIFICATIONS**

| Model                  | BMET-503  |
|------------------------|---|
| рН                     |   |
| Range                  | -2.00 to 20.00 pH                                   |
| Resolution             | 0.1, 0.01 pH  |
| Accuracy               | ± 0.01 pH   |
| Calibration Points     | Up to 5   |
| Standard Customization | Yes   |
| Standard Recognition   | NIST, GB and DIN buffers                            |
| mV                     |   |
| Range                  | -2000.0 to 2000.0 mV                                |
| Resolution             | 0.1 mV  |
| Accuracy               | ± 0.3 mV or ± 0.1 % of reading whichever is greater |
| pX                     |   |
| Range                  | - 2.00 to 20.00                                     |
| Resolution             | 0.1, 0.01 pX  |
| Accuracy               | ±0.02 pX  |
| Calibration Points     | Up to 5   |
| ISE                    |   |
| Range                  | 1E-9 to 9.999E9                                     |
| Unit                   | mol/L, mmol/L, g/L, mg/L, μg/L, ppm                 |
| Resolution             | Up to 4 significant digits                          |
| Accuracy               | ± 0.5 %   |
| Calibration Points     | Up to 5   |
| Temperature            |   |
| Range                  | -5 to 110 °C, 23 to 230 °F                          |

| Unit               | °C, °F   |
|--------------------|--|
| Resolution         | 0.1  |
| Accuracy           | ± 0.2  |
| Measurement        |  |
| Reading Mode       | AutoRead( Fast, Medium, Slow), Timed, Continuous |
| Reading Prompts    | Reading, Stable, Locked                          |
| Temp. Compensation | ATC, MTC   |
| Data Management    |  |
| Data Storage       | 500 results each                                 |
| GLP Features       | Yes  |
| Inputs             |  |
| pH Electrode       | BNC(Q9)  |
| Temp./DO Probe     | 4-pin aviation connector                         |
| Outputs            |  |
| USB                | PC   |
| RS 232             | printer  |
| Display Options    |  |
| Backlight          | Yes  |
| Auto Shut-down     | 1~60 min, off                                    |
| IP Rating          | IP54   |
| Date and Time      | Yes  |
| General            |  |
| Power              | AC Adapter, 100-240 V AC input, DC 9 V output    |
| Dimensions         | 242x195x68 mm                                    |
| Weight             | 900 g(1.98 lb)                                   |



#### Biolab Scientific Ltd.