



DRYING OVEN BODR-102

DRYING OVEN BODR-102

With stainless steel interiors and fibreglass insulation between the walls to maximize thermal efficiency, hot air oven effectively sterilizes glassware, instruments and samples. Glass observation window eliminates the need of opening the door. Forced air convection system maintains temperature uniformity.

Used in Drying, Baking, Disinfecting, Sterilization, Laboratory, Research, Engineering, Industry, Thermostat storage, Heating Storage.

Also known as Heating Oven, Laboratory Drying Oven.

BODR-102 DRYING OVEN



Microcomputer PID intelligent temperature controller with digital display

Forced air circulation system ensures temperature uniformity

Stainless steel inner chamber with cold rolling steel electrostatic spraying exterior

Door with double-layer tempered glass observation window

Adjustable air-tight buckle lock and silicone rubber seal ensures tight sealing and prevents heat loss

Over temperature protection and Timer function

SPECIFICATIONS

Model	BODR-102
Capacity	71 L
Temperature Range	RT+20-250°C
Temperature Accuracy	±1°C
Temperature Uniformity	2.0°C
Temperature Resolution	±0.1°C
Timer Range	1-9999 min
Internal Dimension	450Wx450Dx350H mm
Exterior Dimension	860Wx640Dx800H mm
Shelves	2
Weight	54/66 kg
Power	1600 W
Power Supply	220V, 60Hz



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com