



DRYING OVEN BODR-201

DRYING OVEN BODR-201

With stainless steel interiors and fibreglass insulation between the walls to maximize thermal efficiency, hot air oven effectively sterilizes glassware, instruments and samples. Glass observation window eliminates the need of opening the door. Forced air convection system maintains temperature uniformity.

Used in Drying, Baking, Disinfecting, Sterilization, Laboratory, Research, Engineering, Industry, Thermostat storage, Heating Storage.

Also known as Heating Oven, Laboratory Drying Oven.

BODR-201 DRYING OVEN



ALLSENSTM programmable PID control
ALLHEAT™ cavity warm-up technology
ALLFLOW™ perfect air current cycling
Pro-INSULATION™ Insulation technology
SUS304 stainless steel internal material
Build-in memory menu, real-time monitoring
Display parameters: Temperature, Air velocity, Run time, Run/Stop

SPECIFICATIONS

| | |
|-------------------------|--------------------------|
| Model | BODR-201 |
| Capacity | 40 L |
| Temperature Range | RT+5 - 250°C |
| Ambient Temperature | 10-30°C |
| Temperature Accuracy | 0.1°C |
| Temperature Fluctuation | ±1°C(50 - 240°C) |
| Temperature Uniformity | 2%(50 - 240°C) |
| Ambient Humidity | <70% |
| Timer Range | 0-99 h or 0-9999 min |
| Convection Mode | Forced Convection |
| Internal Dimension | 350Wx350Dx350H mm |
| Exterior Dimension | 570Wx580Dx593H mm |
| Package Size | 690x660x680 mm |
| Shelves | 2 |
| Weight | 40/43 kg |
| Power | 770 W |
| Power Supply | Single phase AC220V/50Hz |



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com