



## DRYING OVEN BODR-203

## DRYING OVEN BODR-203

With stainless steel interiors and fibreglass insulation between the walls to maximize thermal efficiency, hot air oven effectively sterilizes glassware, instruments and samples. Glass observation window eliminates the need of opening the door. Forced air convection system maintains temperature uniformity.

Used in Drying, Baking, Disinfecting, Sterilization, Laboratory, Research, Engineering, Industry, Thermostat storage, Heating Storage.

Also known as Heating Oven, Laboratory Drying Oven.

## BODR-203 DRYING OVEN



ALLSENSTM programmable PID control  
ALLHEATTM cavity warm-up technology  
ALLFLOWTM perfect air current cycling  
Pro-INSULATIONTM Insulation technology  
SUS304 stainless steel internal material  
Build-in memory menu, real-time monitoring  
Display parameters: Temperature, Air velocity, Run time, Run/Stop

## SPECIFICATIONS

Model	BODR-203
Capacity	130 L
Temperature Range	RT+5 - 250°C
Ambient Temperature	10-30°C
Temperature Accuracy	0.1°C
Temperature Fluctuation	±1°C(50 - 240°C)
Temperature Uniformity	2%(50 - 240°C)
Ambient Humidity	<70%
Timer Range	0-99 h or 0-9999 min
Convection Mode	Forced Convection
Internal Dimension	550Wx550Dx450H mm
Exterior Dimension	770Wx780Dx693H mm
Package Size	890x860x780 mm
Shelves	2
Weight	65/69 kg
Power	1270 W
Power Supply	Single phase AC220V/50Hz



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)