



DRYING OVEN BODR-306

DRYING OVEN BODR-306

With stainless steel interiors and fibreglass insulation between the walls to maximize thermal efficiency, hot air oven effectively sterilizes glassware, instruments and samples. Glass observation window eliminates the need of opening the door. Forced air convection system maintains temperature uniformity.

Used in Drying, Baking, Disinfecting, Sterilization, Laboratory, Research, Engineering, Industry, Thermostat storage, Heating Storage.

Also known as Heating Oven, Laboratory Drying Oven.

BODR-306 DRYING OVEN



Microcomputer PID intelligent temperature controller with LCD display

Air blower-heater and vertical hot air circulation system ensures temperature uniformity

Stainless steel inner chamber with cold rolling steel electrostatic spraying exterior

Semicircular arcs at corners for easy cleaning

Wide hollow tempered glass observation window

Adjustable air-tight buckle lock and silicone rubber seal ensures tight sealing and prevents heat loss

Easy to assemble and disassemble air duct lateral plate and bottom heater cover

Over temperature protection and Timer function

SPECIFICATIONS

Model	BODR-306
Capacity	625 L
Temperature Range	RT+10-300°C
Ambient Temperature	5-40°C
Temperature Accuracy	±1°C
Temperature Uniformity	±4°C at 180°C
Temperature Resolution	±0.1°C
Timer Range	1-9999 min
Internal Dimension	660Wx760Dx1250H mm
Exterior Dimension	890Wx880Dx1820H mm
Package Size	1060x1080x1970 mm
Shelves	2
Weight	120/160 kg
Power	5000 W
Power Supply	380V, 50Hz



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com