



DRYING OVEN BODR-7001

DRYING OVEN BODR-7001

BODR-7001 DRYING OVEN



Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable

Auto-controller of fan speed to prevent damage to the samples

Large LCD screen to display more data at same time

Self-check function easy to identify problems

Over temperature and temperature difference alarms

There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature

Programmable controller: 7 periods 63 steps, 0~5999min for each periods, fan speed 0 to 100% adjustable

Independent audible and visible temperature-limiting alarm system ensures experiments run safely

RS485 connector can connect computer and printer to record the parameters and the variations of temperature

SPECIFICATIONS

Model	BODR-7001
Capacity	40 L
Electrical requirement	220 V 50 Hz
Controller	Programmable LCD display
Power Consumption	850 W
Temperature Range	RT +10 - 250°C
Display Resolution	0.1°C
Temperature Stability	±1°C
Temperature Uniformity	±2.5%
Shelves	2 pcs
Interior Dimension	350Wx300Dx400H mm
Exterior Dimension	505Wx655Dx600H mm
Timing Range	0~5999 min



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com