



DRYING OVEN BODR-7101

DRYING OVEN BODR-7101

BODR-7101 DRYING OVEN



304 stainless steel, mirror polishing processing, semicircular arcs at corners easy to clean and maintain. The space between the shelves in the chamber is adjustable
PID controller with over temperature alarm and timing function ensures precise and reliable control

Ceramic fiber door seal, which can run at high temperature for a long time and has a long service life

Programmable controller: 7 periods 63 steps, 0 ~5999mins for each period, can preset boot and shutdown time, adjustable circulating fan

Independent over-temperature alarm system ensures experiments running safely

SPECIFICATIONS

Model	BODR-7101
Capacity	50 L
Electrical requirement	AC 380 V 50 HZ
Temperature Range	RT+20°C 400°C
Display Resolution	0.1°C
Temperature Stability	±0.5°C
Ambient Temperature	+5 - 40°C
Power Consumption	3250 W
Internal Dimension	350Wx350Dx400H mm
External Dimension	890Wx700Dx920H mm
Shelves	2 pcs
Timing Range	0~5999 min



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com