



DRYING OVEN BODR-7102

DRYING OVEN BODR-7102

BODR-7102 DRYING OVEN



304 stainless steel, mirror polishing processing, semicircular arcs at corners easy to clean and maintain. The space between the shelves in the chamber is adjustable
PID controller with over temperature alarm and timing function ensures precise and reliable control

Ceramic fiber door seal, which can run at high temperature for a long time and has a long service life

Programmable controller: 7 periods 63 steps, 0 ~5999mins for each period, can preset boot and shutdown time, adjustable circulating fan

Independent over-temperature alarm system ensures experiments running safely

SPECIFICATIONS

Model	BODR-7102
Capacity	100 L
Electrical requirement	AC 380 V 50 HZ
Temperature Range	RT+20°C 400°C
Display Resolution	0.1°C
Temperature Stability	±0.5°C
Ambient Temperature	+5 - 40°C
Power Consumption	4050 W
Internal Dimension	450Wx450Dx450H mm
External Dimension	990Wx790Dx990H mm
Shelves	2 pcs
Timing Range	0~5999 min



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com