



## DRYING OVEN BODR-7103

## DRYING OVEN BODR-7103

### BODR-7103 DRYING OVEN



304 stainless steel, mirror polishing processing, semicircular arcs at corners easy to clean and maintain. The space between the shelves in the chamber is adjustable  
PID controller with over temperature alarm and timing function ensures precise and reliable control

Ceramic fiber door seal, which can run at high temperature for a long time and has a long service life

Programmable controller: 7 periods 63 steps, 0 ~5999mins for each period, can preset boot and shutdown time, adjustable circulating fan

Independent over-temperature alarm system ensures experiments running safely

## SPECIFICATIONS

|                        |                     |
|------------------------|---------------------|
| Model                  | BODR-7103           |
| Capacity               | 220 L               |
| Electrical requirement | AC 380 V 50 HZ      |
| Temperature Range      | RT+20°C 400°C       |
| Display Resolution     | 0.1°C               |
| Temperature Stability  | ±0.5°C              |
| Ambient Temperature    | +5 - 40°C           |
| Power Consumption      | 4900 W              |
| Internal Dimension     | 600Wx600Dx600H mm   |
| External Dimension     | 1140Wx950Dx1140H mm |
| Shelves                | 2 pcs               |
| Timing Range           | 0~5999 min          |



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)