



ELECTRIC OR TABLE BOPT-106

ELECTRIC OR TABLE BOPT-106

Biolab's electric operation table are cost effective, multi performance mobile operating table that meets the requirement of different surgeons. Easy-to-use electronic controls. Operation table equipped with a table top that rotates 180 degrees, and the chest plate, back plate, head plate, and leg plate on this table can all be easily adjusted, allowing for the ideal positioning of patients undergoing medical imaging tests.

Used in Medical unit, Surgery, Operation theatre, cardiovascular, pediatric, gynecology, abdominal, gall bladder, plastic surgery and more.

Also known as Electric surgical table, Electric OR Table, Electric operating table.

BOPT-106 ELECTRIC OR TABLE



The tabletop adopts high quality of carbon plastic plate, and it can slide, which is convenient for C arm exam and X-ray photography

The mattress is wrapped with imported artificial leather. High-density memory sponge is formed in one piece, with no seam

Using electro-hydraulic working principle. Hand held controller and panel controller are available to control various movements Self-locking function is provided to avoid false triggering.

Hydraulic system from HOERBIGER

AC and DC can use at the same time. It has the function of auto-restoration

One press to "A" or "V"

Imported sealing ring

The table support frame is made of aluminum alloy die-casting and will never rust

The base and rails on both sides of the table are 304 stainless steel

Electric braking device, convenient for shifting the table

The leg plate are controlled by imported gas spring. Leg plate is split and detachable

SPECIFICATIONS

Model	BOPT-106
Table Length	2000±100 mm
Table Width	520±20 mm
Height Adjustment	(750~1000) ±50 mm
Tilt (left)/Tilt (Right)	≥18°/≥18°
Trendelenburg/Rev-Trend	≥25°/≥35°
Head board upwards	≥50°
Head board downwards	≥90°
Backboard upwards	≥70°
Backboard downwards	≥30°
Waist board lifting	100±20 mm
Leg board upwards	≥10°
Leg board downwards	≥90°
Leg board outwards	≥180°
Lumbar upper corner "Λ"	≤150°
Lumbar lower corner "v"	≤110°
Horizontal and longitudinal movement	400±30 mm
Standard Accessories	A Pair of Shoulder/Waist Support, A pair of Arm Support, A pair of leg Plate, A screen
Main Voltage AC	220V±22V, 50Hz±1Hz

Input Power VA	400±10%
----------------	---------



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com