



VACUUM OVEN BOVA-502

VACUUM OVEN BOVA-502

With quick heating times and and high precision temperature control, vacuum ovens effectively handle heat and oxygen sensitive materials with unmatched gentleness while drying. Designed to operate with reduced pressures, it ensures quick and effective drying of samples in powder or pellet form.

Used in Biochemical, Pharmaceutical, Healthcare, Agricultural, Environmental protection, disinfection, Sterilization, Drying, Roasting, Laboratory, Research, engineering, Industry,.

Also known as Vacuum Oven, Laboratory Vacuum Oven.

BOVA-502 VACUUM OVEN

Microprocessor Digital controller

Forced air convection maintains temperature uniformity

High quality cold rolled steel sheet exterior and stainless steel SUS304 inner chamber

Silicon rubber sealing ring prevents heat loss

Heat insulating material: PU FOAM + Glass fiber cotton

Non-condensation observation window with light

Temperature Sensor: PT100

Noise level: ≤ 65 dB

Over-load, over heat, over-current and short-circuit protection

SPECIFICATIONS

Model	BOVA-502
Capacity	52.9 L
Temperature Range	RT+10-250°C
Temperature Accuracy	$\pm 2^\circ\text{C}$
Temperature Fluctuation	$\pm 0.5^\circ\text{C}$
Temperature Uniformity	$\pm 2.0^\circ\text{C}$
Temperature Resolution	$\pm 0.1^\circ\text{C}$
Heating Rate	2.0-3.0°C/min
Cooling Rate	1.0-2.0°C/min
Vacuum Degree	< 133 Pa
Timer Range	1-9999 min
Internal Dimension	415Wx370Dx345H mm
Exterior Dimension	720Wx525Dx535H mm
Shelves	2
Noise Level	≤ 65 dB
Weight	92/96 kg
Power	1400 W
Power Supply	120V/220V/240V/380V/415V, 50Hz/60Hz



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
Email: contact@biolabscientific.com | Website: www.biolabscientific.com