



VACUUM OVEN BOVA-7219

VACUUM OVEN BOVA-7219

BOVA-7219 VACUUM OVEN



304 stainless steel, mirror polishing processing, easy to clean and maintain
PID controller with over temperature alarm and timing function ensures precise and reliable control, also save more than 40% heating time
A big dual layer tempered glass on the door provides good observation
Door adjustment system with silicon door gasket ensures better vacuity

SPECIFICATIONS

| | |
|------------------------|---------------------|
| Model | BOVA-7219 |
| Capacity | 30 L |
| Electrical requirement | AC 220 V 50 HZ |
| Controller | LED display |
| Power Consumption | 300 W |
| Temperature range | RT-10 - 65°C |
| Display Resolution | 0.1 |
| Temperature Stability | ±1°C |
| Vacuum Degree | 133 Pa |
| Ambient Temperature | +5 - 40°C |
| Interior Dimension | 320Wx320Dx300H mm |
| Exterior Dimension | 610Wx510Dx490H mm |
| Shelves | 1 pcs |
| Chamber Material | 304 Stainless steel |



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com