



FOAMING CHARACTERISTICS TESTER BPTL-215

FOAMING CHARACTERISTICS TESTER BPTL-215

Petroleum testing is the analysis during upstream, midstream, and downstream production processes of petroleum products. It is most commonly used to test petroleum product, its product components, byproducts of crude oil, fuel, natural gas, upstream oil and gas and other formats of petroleum.

Used in Petroleum Industry, PVC Pipe Industry.

BPTL-215 FOAMING CHARACTERISTICS TESTER



Separated structure, including main unit, gas source controlled. Sputtering turbine stirrer guarantees temperature uniformity. Touch screen operation, segment timing foam volume with buzzer prompt (optional).

SPECIFICATIONS

Model	BPTL-215
Units	Main unit and gas source controller
Flow meter	Electronic, controls flow at 94 ± 5 ml/min (optional)
Air filter	With molecular sieve
Bath	Refrigerated, 360° circulating, complete transparent.
Holding device	Special holding device, can prevent cylinder floating upward very well press block is unnecessary.
Stirrer	Sputtering turbine stirrer guarantees temperature uniformity
Safety device	Avoids over-heating or low liquid level
Operation	Touch screen
Optional	Segment timing foam volume with buzzer prompt.



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com